



US009636455B2

(12) **United States Patent**
Kamen et al.

(10) **Patent No.:** **US 9,636,455 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **SYSTEM, METHOD, AND APPARATUS FOR ESTIMATING LIQUID DELIVERY**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **DEKA Products Limited Partnership**,
Manchester, NH (US)

4,991,433 A 2/1991 Warnaka
5,349,852 A * 9/1994 Kamen A61M 5/162
137/101.31

(72) Inventors: **Dean Kamen**, Bedford, NH (US); **John M. Kerwin**, Manchester, NH (US);
Colin H. Murphy, Cambridge, MA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **DEKA Products Limited Partnership**,
Manchester, NH (US)

EP 467657 A1 1/1992
EP 2260604 6/2013

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1075 days.

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jul. 31, 2013, received in International patent application No. PCT/US2012/071112, 17 pgs.

(Continued)

(21) Appl. No.: **13/723,251**

(22) Filed: **Dec. 21, 2012**

(65) **Prior Publication Data**

US 2013/0204188 A1 Aug. 8, 2013

Primary Examiner — Aarti B Berdichevsky

(74) *Attorney, Agent, or Firm* — James D. Wyninegar, Jr.

(57) **ABSTRACT**

A pump, related system, and related method are provided. The pump includes a reservoir, a port, and a plunger. The reservoir delivers a liquid by discharging the liquid through the port coupled to the reservoir. The plunger has a piston coupled to a shaft and is disposed within the reservoir in sliding engagement with an inner surface of the reservoir. The piston defines a liquid side of the reservoir and a non-liquid side of the reservoir whereby movement of the plunger towards the liquid side of the reservoir discharges liquid through the port. The pump also includes a reference-volume assembly and/or a linear position sensor. The reference-volume assembly is coupled to the reservoir at an opposite end of the reservoir relative to the port and includes a reference-volume chamber in acoustic communication with the non-liquid side of the reservoir, a speaker disposed within the reference-volume chamber, and a reference microphone disposed within the reference-volume chamber. The reference-volume assembly and/or linear position sen-

(Continued)

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/333,574, filed on Dec. 21, 2011, which is a
(Continued)

(51) **Int. Cl.**
A61M 5/168 (2006.01)
A61M 5/145 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61M 5/1684** (2013.01); **A61M 5/1452** (2013.01); **G06F 19/3418** (2013.01); **G06F 19/3468** (2013.01); **G06Q 50/22** (2013.01)

(58) **Field of Classification Search**
CPC A61M 5/16809; A61M 5/16813; A61M 5/1452; A61M 5/168; A61M 5/1684
See application file for complete search history.

